

FIREROCK

- Unique identification code of the product-type:
RW-PL-G-0058-I
- Type and serial number allowing identification of the product: See product label **FIREROCK MW-EN 13162-T3-CS(10)0,5-WS**
- Intended use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **Thermal insulation products for buildings (ThIB)**
- Name, registered trade name or trade mark and contact address of the manufacturer as required under article 11(5): **ROCKWOOL® Polska Sp. z o.o., ul.Kwiatowa 14, 66-131 Cigacice, Poland**
- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
- System of attestation of conformity: **Sistema1+ Sistema 3**
- Notified Certification body **No. 1390 Centrum stavebního inženýrství a.s. Praha**, performed, carried out the initial type testing, the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance **No 1390-CPR-0318/11/P.**
- Not applicable
- Declared Performance in Table 1 and Table 2

Table 1

Essential Characteristics	Clauses in this and other European standard(s) related to essential characteristics	Harmonized standard EN 13162:2012	Declared value / NPD ¹⁾
Reaction to fire	4.2.6 Reaction to fire	Euroclasses	A1
Release of dangerous substances to the indoor environment	4.3.13 Release of dangerous substances	EU level not yet available	^{c)}
Acoustic absorption index	4.3.11 Sound absorption	α_p (AP ^{a)} and α_w (AWi ^{a)} declared	NPD
Impact noise transmission index (for floors)	4.3.9 Dynamic stiffness	s' , SDI ^{a)} declared	NPD
	4.3.10.2 Thickness, d_L	d_L declared and classes for thickness tolerances T6 or T7	NPD
	4.3.10.4 Compressibility c	CPI ^{a)} declared	NPD
	4.3.12 Air flow resistivity	AF _i ^{a)} declared. Direct airborne sound insulation index	NPD
Direct airborne sound insulation index	4.3.12 Air flow resistivity	AF _i ^{a)} declared.	NPD
Continuous glowing combustion	4.3.15 Continuous glowing combustion	EU level not yet available	^{c)}
Thermal resistance	4.2.1 Thermal resistance and thermal conductivity	Declared R and λ if possible	See table 1 0,038 W/mK
	4.2.3 Thickness	T ^{a)} class for thickness tolerance	T3
Water permeability	4.3.7.1 Short term water absorption	WS- declared W_{p_i}	$\leq 1\text{kg/m}^2$
	4.3.7.2 Long term water absorption	WL(P) -declared W_{p_o}	NPD
Water vapour permeability	4.3.8 Water vapour transmission	Declared μ ; (MU ^{a)} or Zi ^{a)}	NPD
Compressive strength	4.3.3 Compressive stress or compressive strength	CS(10) ^{a)} or CS(10(Y)) ^{a)} declared	CS(10)0,5
	4.3.5 Point load	PL(5) ^{a)} declared	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	4.2.7 Durability characteristics	Reaction to fire against ageing	not change with time
Durability of thermal resistance against heat, weathering, ageing/degradation	4.2.1 Thermal resistance and thermal conductivity	Declared R and λ if possible	not change with time
	4.2.7 Durability characteristics	DS(70,-) declared	NPD
	4.3.2 Dimensional stability at specified temperature	The relative changes in thickness	NPD
Tensile/Flexural strength	4.3.2 Dimensional stability under specified temperature and humidity conditions	DS(70,90) declared The relative changes in thickness	NPD
	4.3.4 Tensile strength perpendicular to faces	TRi ^{a)} declared	NPD
Durability of compressive strength against ageing/degradation	4.3.6 Compressive creep	CC(i_1^a / i_2^a) σ_C compressive creep declared X_{ct} and X_t	NPD

¹⁾ No Performance Determined; ^{a)} "a" indicates relevant class of level or declared value; ^{b)} national regulations not available; ^{c)} according to national regulations; see: Safety Use Instruction Sheet

Table 2

Thermal resistance, R_D													
d(mm)	25	30	40	50	-	-	-	-	-	-	-	-	-
$R_D(\text{m}^2\text{K/W})$	0,65	0,75	1,05	1,30	-	-	-	-	-	-	-	-	-


NOTE: R value for thickness not seen in Table 1, is available on product label

NOTE: The information about Maximum Service Temperature, defined according to EN 14706 is available on product's packaging or in informative brochures.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in Table 1 and Table 2 point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified above point 4.

Signed for and on behalf of the manufacturer by:

Frank Christian Bartel
Technical & Production Director
(Name, function)


Signature

Cigacice, 02.01.2014
Place and date of issue